

# Rol-Air

## 2 HP SINGLE STAGE COMPRESSOR DIRECT DRIVE

H SERIES

ASSOCIATE  
ENGINEERING  
CORPORATION

606 S. LAKE STREET, P.O. BOX 346  
HUSTISFORD, WISCONSIN 53034-0346  
PHONE: 920.349.3281  
SALES FAX: 920.349.3691  
SERVICE FAX: 920.349.8861  
www.rolair.net



D2002HPV5



D2002HSSV5

### “ROL-AIR” STANDARD FEATURES

- PUMP:** Rol-Air Quality, Heavy-Duty, Cast-Iron Cylinder, Single Stage, Ball Bearings, Splash Lubricated, Metal Filter/Silencer w/Replaceable Element, and Stainless Steel Reed Valves Combine to Ensure Longer Pump Life.
- MOTOR:** 2 HP, 3400 RPM, Low Amp Draw, Overload Protected with Manual Reset, 115 Volt, 60 Hz, Industrial Grade with Ball Bearings for Greater Durability.

### SPECIFICATIONS

MODEL	HP	TANK CAP.	DIMENSIONS	CU. FT. DISPLACED	CU. FT. FREE AIR @ 100 PSI	APPROX. SHIPPING WEIGHT
D2002HSSV5	2	4.3	L 20" x W 15" x H 17"	7.8	4.0	68 lbs.
D2002HPV5	2	4.5	L 18" x W 16" x H 17"	7.8	4.0	62 lbs.

### STANDARD EQUIPMENT

- Square D Pressure Switch with On/Off Lever
- 110/135 PSI Operating Pressure
- Regulator w/Air Line Pressure Gauge
- Factory Tested
- Universal Quick Disconnect w/Plug
- Safety Relief Valve
- Intake Filter Silencer
- 12 oz. Crankcase Pre-Filled with Oil



# Rol-Air

## 2 HP SINGLE STAGE COMPRESSOR DIRECT DRIVE

H SERIES

ASSOCIATE  
ENGINEERING  
CORPORATION

606 S. LAKE STREET, P.O. BOX 346  
HUSTISFORD, WISCONSIN 53034-0346  
PHONE: 920-349-3281  
SALES FAX: 920.349.3691  
SERVICE FAX: 920.349.8861  
www.rolair.net



D1500HS3



D1500HPV5

### “ROL-AIR” STANDARD FEATURES

**PUMP:** Rol-Air Quality, Heavy-Duty, Cast-Iron Cylinder, Single Stage, Ball Bearings, Metal Filter/Silencer with Replaceable Element, Stainless Steel Reed Valves and Splash Lubrication Ensure Longer Pump Life.

**MOTOR:** 2 HP, 3400 RPM, Overload Protected with Manual Reset, 115 Volt, 60 Hz, Heavy-Duty, Industrial Grade with Ball Bearings for Greater Durability.

### SPECIFICATIONS

MODEL	HP	TANK CAP.	DIMENSIONS	CU. FT. DISPLACED	CU. FT. FREE AIR @ 100 PSI	APPROX. SHIPPING WEIGHT
D1500HS3**	2	2.5	L 21" x W 9" x H 19"	7.8	4.3	51 lbs.
D1500HPV5	2	4.5	L 18" x W 16" x H 17"	7.8	4.3	62 lbs.

### STANDARD EQUIPMENT

- Square D Pressure Switch with On/Off Lever
- Regulator w/Air Line Pressure Gauge
- Universal Quick Disconnect w/Plug
- 4 oz. Crankcase Pre-Filled with Oil
- 110/135 PSI Operating Pressure
- Factory Tested
- Safety Relief Valve
- Replaceable Filter Element

(\*\*) Designed to allow compressor to lay horizontally during transportation only

